

MARK SCHEME for the October/November 2008 question paper

9709/04

9709 MATHEMATICS

Paper 4, maximum raw mark 50

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began.

All Examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

- CIE will not enter into discussions or correspondence in connection with these mark schemes.

CIE is publishing the mark schemes for the October/November 2008 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



| Page 2 | Mark Scheme | Syllabus | Paper |
|--------|--|----------|-------|
| | GCE A/AS LEVEL – October/November 2008 | 9709 | 04 |

Mark Scheme Notes

Marks are of the following three types:

M Method mark, awarded for a valid method applied to the problem. Method marks are not lost for numerical errors, algebraic slips or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, e.g. by substituting the relevant quantities into the formula. Correct application of a formula without the formula being quoted obviously earns the M mark and in some cases an M mark can be implied from a correct answer.

A Accuracy mark, awarded for a correct answer or intermediate step correctly obtained. Accuracy marks cannot be given unless the associated method mark is earned (or implied).

B Mark for a correct result or statement independent of method marks.

- When a part of a question has two or more "method" steps, the M marks are generally independent unless the scheme specifically says otherwise; and similarly when there are several B marks allocated. The notation DM or DB (or dep*) is used to indicate that a particular M or B mark is dependent on an earlier M or B (asterisked) mark in the scheme. When two or more steps are run together by the candidate, the earlier marks are implied and full credit is given.
- The symbol \surd implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect results. Otherwise, A or B marks are given for correct work only. A and B marks are not given for fortuitously "correct" answers or results obtained from incorrect working.
- Note: B2 or A2 means that the candidate can earn 2 or 0.
B2/1/0 means that the candidate can earn anything from 0 to 2.

The marks indicated in the scheme may not be subdivided. If there is genuine doubt whether a candidate has earned a mark, allow the candidate the benefit of the doubt. Unless otherwise indicated, marks once gained cannot subsequently be lost, e.g. wrong working following a correct form of answer is ignored.

- Wrong or missing units in an answer should not lead to the loss of a mark unless the scheme specifically indicates otherwise.
- For a numerical answer, allow the A or B mark if a value is obtained which is correct to 3 s.f., or which would be correct to 3 s.f. if rounded (1 d.p. in the case of an angle). As stated above, an A or B mark is not given if a correct numerical answer arises fortuitously from incorrect working. For Mechanics questions, allow A or B marks for correct answers which arise from taking g equal to 9.8 or 9.81 instead of 10.

| | | | |
|---------------|---|-----------------|--------------|
| Page 3 | Mark Scheme | Syllabus | Paper |
| | GCE A/AS LEVEL – October/November 2008 | 9709 | 04 |

The following abbreviations may be used in a mark scheme or used on the scripts:

| | |
|-----|---|
| AEF | Any Equivalent Form (of answer is equally acceptable) |
| AG | Answer Given on the question paper (so extra checking is needed to ensure that the detailed working leading to the result is valid) |
| BOD | Benefit of Doubt (allowed when the validity of a solution may not be absolutely clear) |
| CAO | Correct Answer Only (emphasising that no "follow through" from a previous error is allowed) |
| CWO | Correct Working Only - often written by a 'fortuitous' answer |
| ISW | Ignore Subsequent Working |
| MR | Misread |
| PA | Premature Approximation (resulting in basically correct work that is insufficiently accurate) |
| SOS | See Other Solution (the candidate makes a better attempt at the same question) |
| SR | Special Ruling (detailing the mark to be given for a specific wrong solution, or a case where some standard marking practice is to be varied in the light of a particular circumstance) |

Penalties

| | |
|-------|---|
| MR -1 | A penalty of MR -1 is deducted from A or B marks when the data of a question or part question are genuinely misread and the object and difficulty of the question remain unaltered. In this case all A and B marks then become "follow through $\sqrt{}$ " marks. MR is not applied when the candidate misreads his own figures - this is regarded as an error in accuracy. An MR -2 penalty may be applied in particular cases if agreed at the coordination meeting. |
| PA -1 | This is deducted from A or B marks in the case of premature approximation. The PA -1 penalty is usually discussed at the meeting. |

| Page 4 | Mark Scheme | Syllabus | Paper |
|--------|--|----------|-------|
| | GCE A/AS LEVEL – October/November 2008 | 9709 | 04 |

| | | |
|--|------|--|
| 1 (i) (a) $10 - 8\cos\theta$ | B1 | |
| (b) $8\sin\theta$ | B1 | [2] |
| ----- | | |
| (ii) | M1 | For using $X^2 + Y^2 = R^2$ or for using the cosine rule in the relevant triangle |
| $(10 - 8\cos\theta)^2 + (8\sin\theta)^2 = 8^2$ or | | |
| $10^2 + 8^2 - 2 \times 10 \times 8 \cos\theta = 8^2$ | A1ft | |
| $\cos\theta = 5/8$ | A1 | [3] AG |
| First alternative for (ii) | | |
| $[\cos\phi = (10 - 8\cos\theta)/8$ and $\sin\phi = 8\sin\theta/8]$ | M1 | For using $\cos\phi = X/R$ and $\sin\phi = Y/R$ |
| $8\cos\phi = (10 - 8\cos\theta)$ and $\phi = \theta$ | A1ft | |
| $\cos\theta = 5/8$ | A1 | AG |
| Second alternative for (ii) | | |
| $[5, \sqrt{39}, 64]$ | M1 | For assuming $\cos\theta = 5/8$ and hence finding exact values of $\sin\theta$, X, Y and $X^2 + Y^2$ |
| $R = 8$ | A1 | |
| → assumption correct | A1 | |
| SR for (ii) (max 2/3) | | |
| | M1 | For assuming $\cos\theta = 5/8$ and hence finding $\theta = 51.3^\circ$ and the values of X, Y and $X^2 + Y^2$ |
| $R = 8$ or 8.0 or 8.00 or 7.997.. | | |
| → assumption correct | A1 | |
| 2 | | |
| | M1 | For resolving forces parallel to the plane (either case) |
| $[R = 197, F = 63.0]$ | M1 | For using $F = 0.32R$ and $R = 20g\cos 10^\circ$ (or $20g\sin 10^\circ$ if this is part of a consistent sin/cos interchange) |
| (i) $P = F + 20g\sin 10^\circ$ | A1 | |
| Least magnitude is 97.8N | A1 | |

| Page 5 | Mark Scheme | Syllabus | Paper |
|--------|--|----------|-------|
| | GCE A/AS LEVEL – October/November 2008 | 9709 | 04 |

| | | |
|---|------|--|
| (ii) $P = F - 20g \sin 10^\circ$ | A1ft | ft with $P \cos 10^\circ$ instead of P or sign error or cos instead of sin in component of weight |
| Least magnitude is 28.3N | A1 | [6] |
| SR (for candidates who omit g) (max 3/6) | | |
| For $P = F + 20 \sin 10^\circ$ in (i) and | | |
| $P = F - 20 \sin 10^\circ$ in (ii) | B1 | |
| | M1 | For using $F = 0.32R$ and $R = 20 \cos 10^\circ$ |
| Least magnitude is 9.78N in (i) and 2.83 in (ii) | A1 | |
| 3 (i) | | |
| | M1 | For applying Newton's second law (3 terms) |
| $F - 900 = 1200a$ | A1 | |
| $[18000/25 - 900 = 1200a]$ | M1 | For using $F = P/v$ |
| Deceleration is 0.15ms^{-2} | A1 | [4] Accept $a = -0.15$ |
| ----- | | |
| (ii) $18000/v - 900 = 0$ | B1 | |
| Least speed is 20ms^{-1} | B1 | [2] AG |
| 4 $[s = (0 + 0.5)/2 \times 7]$ | | |
| $s = 1.75 \text{m}$ | M1 | For using $(u + v)/2 = s/t$ |
| PE gain = $160g \times 1.75$ | A1 | May be implied |
| KE gain = $\frac{1}{2} 160 \times 0.5^2$ | B1ft | |
| $[WD = 2800 + 20]$ | B1 | |
| Work done is 2820J | M1 | For using $WD = PE \text{ gain} + KE \text{ gain}$ |
| | A1 | [6] |
| SR (max 4/6) for candidates who use a non-energy method | | |
| $[s = (0 + 0.5)/2 \times 7]$ | M1 | For using $(u + v)/2 = s/t$ |
| $s = 1.75 \text{m}$ | A1 | |
| $[a = 1/14, T = 160g + 160/14, WD = 1611.4... \times 1.75]$ | M1 | For finding the acceleration and using Newton's second law (3 terms) to find the tension in the rope, then multiplying by the distance |
| Work done is 2820J | A1 | |

| Page 6 | Mark Scheme | Syllabus | Paper |
|--------|--|----------|-------|
| | GCE A/AS LEVEL – October/November 2008 | 9709 | 04 |

| | | | |
|-----------|---|--------------|---|
| 5 (i) (a) | [5 = 0 + 2a] | M1 | For using $v = u + at$ with $u = 0$ |
| | Acceleration is 2.5ms^{-2} | A1 [2] | |
| (b) | | M1 | For applying Newton's second law to A (3 terms): (can be scored in (ii) by applying Newton's second law to B instead) |
| | $0.5g - T = 0.5 \times 2.5$ | A1ft | |
| | Tension is 3.75N | A1 [3] | |
| (ii) | $T - mg = 2.5m$ or $0.5g - mg = 0.5 \times 2.5 + 2.5m$ | B1ft | ft from $T - 0.5g = 0.5 \times 2.5$ in (i) (b) to allow $mg - T = 2.5m$ or $mg - 0.5g = 0.5 \times 2.5 + 2.5m$ |
| | $[(10 + 2.5)m = 3.75]$ $m = 0.3$ | M1 A1 [3] | For solving 3 term equation for m |

| | | | |
|--|---|--------------|---|
| 6 (i) | <ul style="list-style-type: none"> v is single valued, continuous and positive for $0 < t < 1000$. 1st segment has +ve slope And two or more of <ul style="list-style-type: none"> $v(0) = 0$ $v(1000) = 0$ 2nd segment has zero slope 3rd segment has -ve slope Correct sketch | M1 | For sketching a graph consisting of 3 straight line segments, for which (see left): |
| | | A1 [2] | |
| (ii) | | M1 | For using 'area under graph' represents distance of 20000m |
| | $\frac{1}{2}(600 + 1000)V = 20\,000$ $V = 25$ | A1 A1 [3] | |
| SR for candidates who assume 1 st and 3 rd time intervals are each 200 s (max 2/3) | | | |
| | $\frac{1}{2} V \times 200 + V \times 600 + \frac{1}{2} V \times 200 = 20000$ | B1 | |
| | $V = 25$ | B1 | |

| Page 7 | Mark Scheme | Syllabus | Paper |
|--------|--|----------|-------|
| | GCE A/AS LEVEL – October/November 2008 | 9709 | 04 |

| | | | |
|---|------|--|------|
| (iii) $[V/t_1 = 0.15 \rightarrow t_1 = 166.6\dots]$ | M1 | For using the gradient property for acceleration (or $v = 0 + at$) to find t_1 . | |
| $t_3 = 233.3\dots$ | A1ft | ft $400 - V/0.15$ | |
| $[s_3 = \frac{1}{2} 233.3\dots \times 25]$ | DM1 | For using the area property for distance or $(u + v)/2 = s/t$. Depends on previous M1 | |
| Distance is 2920m | A1 | [4] | |
| Alternatively | | | |
| | | For using $V^2 = 2 \times 0.15 s_1$ | M1 |
| | | $[\rightarrow s_1 = 2083.3\dots]$ | |
| | | $s_2 = 15000$ (ft 600V) | B1ft |
| | | For $s_3 = 20000 - s_1 - s_2$ | DM1 |
| | | Distance is 2920m | A1 |

| | | | |
|--|------|--|--|
| 7 (i) $[v^2 = 2 \times 10 \times 1.25$ or $\frac{1}{2} mv^2 = mg(1.25)$, $1.25 = \frac{1}{2} 10t^2]$ | M1 | For using $s = 1.25$ and $a = 10$ to find either v or t | |
| Speed of P is 5ms^{-1} | A1 | | |
| Time taken is 0.5s | A1 | [3] | |
| (ii) | M1 | For using $v = \int a(t) dt$ | |
| $v = 10t - 0.15t^2$ (+C) | A1 | | |
| $v = 10t - 0.15t^2 + 5$ | A1ft | ft wrong answer in (i) | |
| | M1 | For using $x = \int v(t) dt$ | |
| $x = 5t^2 - 0.05t^3 + 5t$ | A1ft | | |
| $[x = 5 \times 2.5^2 - 0.05 \times 2.5^3 + 5 \times 2.5$ (= 42.97)] | DM1 | For substituting $t = 3 - t_1$ in $x(t)$. Depends on both previous M1s. | |
| Distance OP is 44.2m | A1 | [7] | |