

# Cambridge International AS & A Level

---

**PHYSICS****9702/42**

Paper 4 A Level Structured Questions

**May/June 2025**

MARK SCHEME

Maximum Mark: 100

---

Published

---

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the May/June 2025 series for most Cambridge IGCSE, Cambridge International A and AS Level components, and some Cambridge O Level components.

---

This document consists of **18** printed pages.

These general marking principles must be applied by all examiners when marking candidate answers. They should be applied alongside the specific content of the mark scheme or generic level descriptions for a question. Each question paper and mark scheme will also comply with these marking principles.

**GENERIC MARKING PRINCIPLE 1:**

Marks must be awarded in line with:

- the specific content of the mark scheme or the generic level descriptors for the question
- the specific skills defined in the mark scheme or in the generic level descriptors for the question
- the standard of response required by a candidate as exemplified by the standardisation scripts.

**GENERIC MARKING PRINCIPLE 2:**

Marks awarded are always **whole marks** (not half marks, or other fractions).

**GENERIC MARKING PRINCIPLE 3:**

Marks must be awarded **positively**:

- marks are awarded for correct/valid answers, as defined in the mark scheme. However, credit is given for valid answers which go beyond the scope of the syllabus and mark scheme, referring to your Team Leader as appropriate
- marks are awarded when candidates clearly demonstrate what they know and can do
- marks are not deducted for errors
- marks are not deducted for omissions
- answers should only be judged on the quality of spelling, punctuation and grammar when these features are specifically assessed by the question as indicated by the mark scheme. The meaning, however, should be unambiguous.

**GENERIC MARKING PRINCIPLE 4:**

Rules must be applied consistently, e.g. in situations where candidates have not followed instructions or in the application of generic level descriptors.

**GENERIC MARKING PRINCIPLE 5:**

Marks should be awarded using the full range of marks defined in the mark scheme for the question (however; the use of the full mark range may be limited according to the quality of the candidate responses seen).

**GENERIC MARKING PRINCIPLE 6:**

Marks awarded are based solely on the requirements as defined in the mark scheme. Marks should not be awarded with grade thresholds or grade descriptors in mind.

**Science-Specific Marking Principles**

- 1 Examiners should consider the context and scientific use of any keywords when awarding marks. Although keywords may be present, marks should not be awarded if the keywords are used incorrectly.
- 2 The examiner should not choose between contradictory statements given in the same question part, and credit should not be awarded for any correct statement that is contradicted within the same question part. Wrong science that is irrelevant to the question should be ignored.
- 3 Although spellings do not have to be correct, spellings of syllabus terms must allow for clear and unambiguous separation from other syllabus terms with which they may be confused (e.g. ethane / ethene, glucagon / glycogen, refraction / reflection).
- 4 The error carried forward (ecf) principle should be applied, where appropriate. If an incorrect answer is subsequently used in a scientifically correct way, the candidate should be awarded these subsequent marking points. Further guidance will be included in the mark scheme where necessary and any exceptions to this general principle will be noted.

**5 'List rule' guidance**

For questions that require ***n*** responses (e.g. State **two** reasons ...):

- The response should be read as continuous prose, even when numbered answer spaces are provided.
- Any response marked *ignore* in the mark scheme should not count towards ***n***.
- Incorrect responses should not be awarded credit but will still count towards ***n***.
- Read the entire response to check for any responses that contradict those that would otherwise be credited. Credit should **not** be awarded for any responses that are contradicted within the rest of the response. Where two responses contradict one another, this should be treated as a single incorrect response.
- Non-contradictory responses after the first ***n*** responses may be ignored even if they include incorrect science.

**6 Calculation specific guidance**

Correct answers to calculations should be given full credit even if there is no working or incorrect working, **unless** the question states 'show your working'.

For questions in which the number of significant figures required is not stated, credit should be awarded for correct answers when rounded by the examiner to the number of significant figures given in the mark scheme. This may not apply to measured values.

For answers given in standard form (e.g.  $a \times 10^n$ ) in which the convention of restricting the value of the coefficient ( $a$ ) to a value between 1 and 10 is not followed, credit may still be awarded if the answer can be converted to the answer given in the mark scheme.

Unless a separate mark is given for a unit, a missing or incorrect unit will normally mean that the final calculation mark is not awarded. Exceptions to this general principle will be noted in the mark scheme.

**7 Guidance for chemical equations**

Multiples / fractions of coefficients used in chemical equations are acceptable unless stated otherwise in the mark scheme.

State symbols given in an equation should be ignored unless asked for in the question or stated otherwise in the mark scheme.

**Annotations guidance for centres**

Examiners use a system of annotations as a shorthand for communicating their marking decisions to one another. Examiners are trained during the standardisation process on how and when to use annotations. The purpose of annotations is to inform the standardisation and monitoring processes and guide the supervising examiners when they are checking the work of examiners within their team. The meaning of annotations and how they are used is specific to each component and is understood by all examiners who mark the component.

We publish annotations in our mark schemes to help centres understand the annotations they may see on copies of scripts. Note that there may not be a direct correlation between the number of annotations on a script and the mark awarded. Similarly, the use of an annotation may not be an indication of the quality of the response.

The annotations listed below were available to examiners marking this component in this series.

**Annotations**

Annotation	Meaning
<b>AE</b>	arithmetic error
<b>BOD</b>	benefit of the doubt given
<b>CON</b>	contradiction in response, mark not awarded
	correct point or mark awarded
<b>ECF</b>	error carried forward applied
<b>SF</b>	error in number of significant figures
<b>I</b>	incorrect or insufficient point ignored while marking the rest of the response
<b>XP</b>	incorrect physics
	incorrect point or mark not awarded
	information missing or insufficient for credit

Annotation	Meaning
<b>MO</b>	mandatory mark not awarded
<b>SEEN</b>	point has been noted, but no credit has been given or blank page seen
<b>POT</b>	power of ten error
<b>TE</b>	transcription error

### Abbreviations

/	Alternative and acceptable answers for the same marking point.
( )	Bracketed content indicates words which do not need to be explicitly seen to gain credit but which indicate the <b>context</b> for an answer. The context does not need to be seen but if a context is given that is incorrect then the mark should not be awarded.
—	Underlined content must be present in answer to award the mark. This means either the exact word or another word that has the same technical meaning.

**Mark categories**

<b>B</b> marks	These are <u>independent</u> marks, which do not depend on other marks. For a <b>B</b> mark to be awarded, the point to which it refers must be seen specifically in the candidate's answer.
<b>M</b> marks	These are <u>mandatory</u> marks upon which <b>A</b> marks later depend. For an <b>M</b> mark to be awarded, the point to which it refers must be seen specifically in the candidate's answer. If a candidate is not awarded an <b>M</b> mark, then the later <b>A</b> mark cannot be awarded either.
<b>C</b> marks	<p>These are <u>compensatory</u> marks which can be awarded even if the points to which they refer are not written down by the candidate, providing subsequent working gives evidence that they must have known them. For example, if an equation carries a <b>C</b> mark and the candidate does not write down the actual equation but does correct working which shows the candidate knew the equation, then the <b>C</b> mark is awarded.</p> <p>If a correct answer is given to a numerical question, all of the preceding <b>C</b> marks are awarded automatically. It is only necessary to consider each of the <b>C</b> marks in turn when the numerical answer is not correct.</p>
<b>A</b> marks	These are <u>answer</u> marks. They may depend on an <b>M</b> mark or allow a <b>C</b> mark to be awarded by implication.

Question	Answer	Marks
1(a)	angle (subtended at centre of a circle) when arc (length) = radius	<b>B1</b>
1(b)(i)	$v = r\omega$ $\omega = 17 / 0.46$ $= 37 \text{ rad s}^{-1}$	<b>C1</b> <b>A1</b>
1(b)(ii)	$T = 2\pi r / v$ or $T = 2\pi / \omega$ $= 2\pi \times 0.46 / 17$ or $2\pi / 37$ $= 0.17 \text{ s}$	<b>C1</b> <b>A1</b>
1(b)(iii)	distance = $2\pi \times 0.038 = 0.24 \text{ m}$	<b>A1</b>
1(b)(iv)	angle = arc length / radius $= 0.24 / 0.15$ $= 1.6 \text{ rad}$	<b>C1</b> <b>A1</b>
1(c)	point X moves through a smaller distance in the same time or (linear) speed of movement of point X / chain decreases or (linear) speed of (circumference of) both cogs decreases angular speed (of pedals) decreases	<b>B1</b> <b>B1</b>

Question	Answer	Marks
2(a)(i)	direction of force	B1
	force acting on a (test) mass	B1
2(a)(ii)	at least four radial lines from the Earth's surface, equally spaced around the surface	B1
	arrows indicating direction towards Earth	B1
2(b)(i)	top pole labelled S and bottom pole labelled N	B1
2(b)(ii)	solenoid field pattern at the poles:  at least two field lines either side of both poles, close to the poles, clustered closely together, leaving the surface approximately perpendicularly to the surface and curving away from the axis of the poles as their distance from the surface increases	B1
	solenoid field pattern above the equator:  at least one field line either side of the Earth connecting two points on the surface that are on the same side of the poles, one north of the equator and one south of it, passing above the surface near the magnetic equator approximately parallel to the surface	B1
	(around the surface) lines are evenly spaced	B1
	all lines perpendicular to surface <b>or</b> pointing down towards surface (at all points around the surface)	B1

Question	Answer	Marks
2(c)(ii)	<p><i>Any three bulleted points from:</i></p> <ul style="list-style-type: none"> <li>• strongest at the poles</li> <li>• weakest near the Equator</li> </ul> <p><i>Up to two points from:</i></p> <ul style="list-style-type: none"> <li>• perpendicular to surface at the poles</li> <li>• parallel to the surface near the Equator</li> <li>• angle to surface increases from Equator to poles</li> </ul>	<b>B3</b>

Question	Answer	Marks
3(a)	(thermal) energy per unit mass (to cause temperature change)	<b>B1</b>
	(thermal) energy per unit change in temperature	<b>B1</b>
3(b)(i)	density = mass / volume	<b>C1</b>
	$\text{mass} = 2.700 \times 10^3 \times 3.612 \times 10^{-3}$ $= 9.752 \text{ kg}$	<b>A1</b>
3(b)(ii)	$\text{volume} = 3.612 \times 10^{-3} \times (2.700 / 2.620) = 3.722 \times 10^{-3} \text{ m}^3$ <p><b>or</b></p> $\text{volume} = 9.752 / (2.620 \times 10^3) = 3.722 \times 10^{-3} \text{ m}^3$	<b>A1</b>

Question	Answer	Marks
3(b)(iii)	$W = p\Delta V$  $= 1.01 \times 10^5 \times (3.722 - 3.612) \times 10^{-3}$  $= 11.1 \text{ J}$	<b>C1</b>
3(b)(iv)	volume (of block) increases  work is done against the atmosphere so work done (on block) is negative	<b>B1</b>  <b>B1</b>
3(b)(v)	thermal energy = $(4.38 \times 10^6) + 11.1$  specific heat capacity = $(4.38 \times 10^6) / (9.75 \times 500)$  $= 898 \text{ J kg}^{-1} \text{ }^{\circ}\text{C}^{-1}$	<b>B1</b>  <b>C1</b>  <b>A1</b>
3(c)	work done is negligible compared with (change in) internal energy so (answer in (b)(v) would be) unchanged	<b>B1</b>

Question	Answer	Marks
4(a)(i)	thermodynamic temperature	<b>B1</b>
4(a)(ii)	molar gas constant	<b>B1</b>
4(b)(i)	$m$ : mass of one molecule (of the gas)	<b>B1</b>
	$\langle c^2 \rangle$ : mean-square speed (of molecules)	<b>B1</b>
4(b)(ii)	$NBT/A = \frac{1}{3} Nm\langle c^2 \rangle$	<b>M1</b>
	clear use of $E_K = \frac{1}{2} m\langle c^2 \rangle$ leading to $E_K = 3BT/2A$	<b>A1</b>
4(c)	line with positive gradient passing through the origin	<b>B1</b>
	smooth curve with decreasing positive gradient	<b>B1</b>

Question	Answer	Marks
5(a)	(motion in which) acceleration is (directly) proportional to displacement	<b>B1</b>
	(motion in which) acceleration is (always) in the opposite <u>direction</u> to displacement <b>or</b> acceleration is (always) directed towards a fixed point	<b>B1</b>
5(b)(i)	period = $2\pi / 16$  = 0.39 s	<b>A1</b>
5(b)(ii)	$v_0 = \omega x_0$ <b>or</b> $v_0 = \omega \sqrt{(x_0^2 - 0^2)}$	<b>C1</b>
	$x_0 = 0.56 / 16$  = 0.035 m	<b>A1</b>
5(b)(iii)	$v = \pm 16 \sqrt{(0.0352 - x^2)}$	<b>A1</b>
5(b)(iv)	closed loop surrounding the origin	<b>B1</b>
	loop crosses $v = 0$ at maximum values of $x$ at $x = \pm 3.5$ cm	<b>B1</b>
	loop crosses $x = 0$ at maximum values of $v$ at $v = \pm 0.56 \text{ m s}^{-1}$	<b>B1</b>

Question	Answer	Marks
6(a)	plate X marked as negative and plate Y marked as positive	B1
6(b)(i)	$E = V/x$ $= (58 \times 10^3) / 0.041$ $= 1.4 \times 10^6 \text{ N C}^{-1}$	C1 A1
6(b)(ii)	$ma = eE$ $a = (1.60 \times 10^{-19} \times 1.41 \times 10^6) / (9.11 \times 10^{-31})$ $= 2.5 \times 10^{17} \text{ m s}^{-2}$	C1 A1
6(c)(i)	$eV = hc/\lambda$ <b>or</b> $eV = hf \text{ and } f = c/\lambda$ $(1.60 \times 10^{-19} \times 58 \times 10^3) = (6.63 \times 10^{-34} \times 3.00 \times 10^8) / \lambda$	C1 M1
6(c)(ii)	X-rays	B1
6(c)(iii)	<i>Any two points from:</i> <ul style="list-style-type: none"> <li>waves are passed into structure and transmitted waves detected</li> <li>different parts of the structure absorb different fractions of energy</li> <li>difference in detected / transmitted <u>intensities</u> used (to form image)</li> </ul>	B2

Question	Answer	Marks
7(a)	$V_C = V_R$	<b>B1</b>
7(b)(i)	$C = Q / V$  $= (7.2 \times 10^{-3}) / 12$ ( $= 6.0 \times 10^{-4}$ F)  $= 600 \mu\text{F}$	<b>C1</b>  <b>A1</b>
7(b)(ii)	$R = V / I$  $= 12 / (1.5 \times 10^{-3})$ ( $= 8000 \Omega$ )  $= 8.0 \text{ k}\Omega$	<b>C1</b>  <b>A1</b>
7(b)(iii)	$\tau = RC$  $= 8000 \times 6.0 \times 10^{-4}$  $= 4.8 \text{ s}$	<b>C1</b>  <b>A1</b>
7(c)	<p><i>Any two points from:</i></p> <ul style="list-style-type: none"> <li>charge and current are both (directly) proportional to voltage</li> <li>charge is (directly) proportional to current</li> <li>current is the rate of change of charge</li> </ul> <p>Q is proportional to the rate of change of Q (so exponential variation)</p>	<b>B2</b>  <b>B1</b>

Question	Answer	Marks
8(a)(i)	half-wave (rectification)	<b>B1</b>
8(a)(ii)	$V_0 = 6.0 \times \sqrt{2}$ $= 8.5 \text{ V}$	<b>A1</b>
8(b)(i)	$P = V^2 / R$ $P_0 = 8.5^2 / 45$ $= 1.6 \text{ W}$	<b>C1</b>
8(b)(ii)	<p>two humps of width <math>0.5T</math> and two sections of zero power of width <math>0.5T</math></p> <p>all humps drawn have width <math>0.5T</math>, minima at <math>P = 0</math> and peaks at <math>P = P_0</math></p> <p>correct sinusoidal shape, with smooth troughs sitting on <math>t</math>-axis at <math>P = 0</math></p>	<b>B1</b>
8(b)(iii)	<p>mean power within each hump is <math>\frac{1}{2} P_0</math> from the symmetry of the curve</p> <p>additional half factor from removal of half of the power in each cycle</p>	<b>B1</b>
8(b)(iv)	$\langle P \rangle = V_{\text{r.m.s.}}^2 / R$ $V_{\text{r.m.s.}} = \sqrt{[(1.6 / 4) \times 45]}$ $= 4.2 \text{ V}$	<b>A1</b>

Question	Answer	Marks
9(a)	emission of electrons (from a metal surface)	B1
	when electromagnetic radiation is incident (on surface / electrons)	B1
9(b)(i)	current falls to zero when applied voltage equals energy per unit charge of emitted electrons	B1
	energy of photon depends on frequency	B1
	maximum energy of electron depends on energy of photon	B1
9(b)(ii)	<p><i>Any three points from:</i></p> <ul style="list-style-type: none"> <li>threshold frequency = <math>1.5 \times 10^{15}</math> Hz</li> <li>threshold wavelength = <math>2.0 \times 10^{-7}</math> m</li> <li>work function = 6.2 eV (or <math>9.9 \times 10^{-19}</math> J)</li> <li>Planck constant = <math>6.6 \times 10^{-34}</math> J s (not <math>6.63 \times 10^{-34}</math> J s)</li> <li>number per unit time (of photons / electrons) = <math>1.7 \times 10^{16}</math> s<sup>-1</sup> (in stage 1)</li> <li>power of incident radiation = 0.028 W (in stage 1)</li> </ul>	B3

Question	Answer	Marks															
10(a)	(decay is) not affected by external / environmental factors	B1															
10(b)(i)	<p>half-life of X = <math>2T</math> <b>and</b> half-life of Y = <math>3T</math></p> <p>both samples show decay constant, in terms of <math>1/T</math>, equal to <math>\ln 2 / \text{half-life}</math> (decay constant of X = <math>\ln 2 / 2T</math> and decay constant of Y = <math>\ln 2 / 3T</math> if both half-lives correct)</p> <p>both samples show <math>N_0</math>, in terms of <math>AT</math>, equal to initial activity / decay constant (<math>N_0</math> for X = <math>8AT / \ln 2</math> and <math>N_0</math> for Y = <math>3AT / \ln 2</math> if both decay constants correct)</p> <p>(Fully correct table:</p> <table border="1"> <thead> <tr> <th></th> <th>half-life</th> <th>decay constant</th> <th><math>A_0</math></th> <th><math>N_0</math></th> </tr> </thead> <tbody> <tr> <td>X</td> <td><math>2T</math></td> <td><math>\ln 2 / 2T</math></td> <td><math>4A</math></td> <td><math>8AT / \ln 2</math></td> </tr> <tr> <td>Y</td> <td><math>3T</math></td> <td><math>\ln 2 / 3T</math></td> <td><math>A</math></td> <td><math>3AT / \ln 2</math></td> </tr> </tbody> </table> <p>)</p>		half-life	decay constant	$A_0$	$N_0$	X	$2T$	$\ln 2 / 2T$	$4A$	$8AT / \ln 2$	Y	$3T$	$\ln 2 / 3T$	$A$	$3AT / \ln 2$	B1
	half-life	decay constant	$A_0$	$N_0$													
X	$2T$	$\ln 2 / 2T$	$4A$	$8AT / \ln 2$													
Y	$3T$	$\ln 2 / 3T$	$A$	$3AT / \ln 2$													
10(b)(ii)	<p>correct substitution of <math>A_0</math> and <math>\lambda</math> into <math>A_0 \exp(-\lambda t)</math> for sample X or sample Y</p> <p><math>4A \exp(-t \ln 2 / 2T) = A \exp(-t \ln 2 / 3T)</math></p> <p><math>t = 12T</math></p>	C1															
10(c)	<p><i>Any two points from:</i></p> <ul style="list-style-type: none"> <li>• (radiation) emitted in all directions, not just in direction of detector</li> <li>• some radiation absorbed by air / sample / window of detector</li> <li>• some radiation may not register even though it reaches detector</li> </ul>	B2															