

**MARK SCHEME for the October/November 2011 question paper
for the guidance of teachers**

9702 PHYSICS

9702/23

Paper 2 (AS Structured Questions), maximum raw mark 60

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

- Cambridge will not enter into discussions or correspondence in connection with these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2011 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.

Page 2	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2011	9702	23

- 1 (a) scalar has magnitude/size, vector has magnitude/size and direction B1 [1]
- (b) acceleration, momentum, weight B2 [2]
 (–1 for each addition or omission but stop at zero)
- (c) (i) horizontally: $7.5 \cos 40^\circ / 7.5 \sin 50^\circ = 5.7(45) / 5.75$ not 5.8 N A1 [1]
 (ii) vertically: $7.5 \sin 40^\circ / 7.5 \cos 50^\circ = 4.8(2)$ N A1 [1]
- (d) *either* correct shaped triangle M1
 correct labelling of two forces, three arrows and two angles A1
or correct resolving: $T_2 \cos 40^\circ = T_1 \cos 50^\circ$ (B1)
 $T_1 \sin 50^\circ + T_2 \sin 40^\circ = 7.5$ (B1)
 $T_1 = 5.7(45)$ (N) A1
 $T_2 = 4.8$ (N) A1 [4]
 (allow ± 0.2 N for scale diagram)
- 2 (a) 1. constant velocity / speed B1 [1]
 2. *either* constant / uniform decrease (in velocity/speed)
or constant rate of decrease (in velocity/speed) B1 [1]
- (b) (i) distance is area under graph for both stages C1
 stage 1: distance $(18 \times 0.65) = 11.7$ (m)
 stage 2: distance $= (9 \times [3.5 - 0.65]) = 25.7$ (m)
 total distance $= 37.(4)$ m A1 [2]
 (–1 for misreading graph)
 {for stage 2, allow calculation of acceleration (6.32 ms^{-2})
 and then $s = (18 \times 2.85) + \frac{1}{2} \times 6.32 (2.85)^2 = 25.7$ m}
- (ii) *either* $F = ma$ *or* $E_K = \frac{1}{2}mv^2$ C1
 $a = (18 - 0)/(3.5 - 0.65)$ $E_K = \frac{1}{2} \times 1250 \times (18)^2$ C1
- $F = 1250 \times 6.3 = 7900$ N *or* $F = \frac{1}{2} \times 1250 \times (18)^2 / 25.7 = 7900$ N A1 [3]
or initial momentum $= 1250 \times 18$ (C1)
 $F = \text{change in momentum} / \text{time taken}$ (C1)
 $F = (1250 \times 18) / 2.85 = 7900$ (A1)
- (c) (i) stage 1: *either* half / less distance as speed is half / less
or half distance as the time is the same
or sensible discussion of reaction time B1 [1]
- (ii) stage 2: *either* same acceleration and $s = v^2 / 2a$ *or* v^2 is $\frac{1}{4}$
 $\frac{1}{4}$ of the distance B1
 B1 [2]

Page 3	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2011	9702	23

- 3 (a) (i) power = work done per unit time / energy transferred per unit time / rate of work done B1 [1]
- (ii) Young modulus = stress / strain B1 [1]
- (b) (i) 1. $E = T / (A \times \text{strain})$ (allow strain = ϵ) C1
 $T = E \times A \times \text{strain} = 2.4 \times 10^{11} \times 1.3 \times 10^{-4} \times 0.001$ M1
 $= 3.12 \times 10^4 \text{ N}$ A0 [2]
2. $T - W = ma$ C1
 $[3.12 \times 10^4 - 1800 \times 9.81] = 1800a$ C1
 $a = 7.52 \text{ ms}^{-2}$ A1 [3]
- (ii) 1. $T = 1800 \times 9.81 = 1.8 \times 10^4 \text{ N}$ A1 [1]
2. potential energy gain = mgh C1
 $= 1800 \times 9.81 \times 15$
 $= 2.7 \times 10^5 \text{ J}$ A1 [2]
- (iii) $P = Fv$ C1
 $= 1800 \times 9.81 \times 0.55$ C1
input power = $9712 \times (100/30) = 32.4 \times 10^3 \text{ W}$ A1 [3]
- 4 (a) p.d. = $\frac{\text{energy transformed from electrical to other forms}}{\text{unit charge}}$ B1
- e.m.f. = $\frac{\text{energy transformed from other forms to electrical}}{\text{unit charge}}$ B1 [2]
- (b) (i) sum of e.m.f.s (in a closed circuit) = sum of potential differences B1 [1]
- (ii) $4.4 - 2.1 = I \times (1.8 + 5.5 + 2.3)$ M1
 $I = 0.24 \text{ A}$ A1 [2]
- (iii) arrow (labelled) I shown anticlockwise A1 [1]
- (iv) 1. $V = I \times R = 0.24 \times 5.5 = 1.3(2) \text{ V}$ A1 [1]
2. $V_A = 4.4 - (I \times 2.3) = 3.8(5) \text{ V}$ A1 [1]
3. either $V_B = 2.1 + (I \times 1.8)$ or $V_B = 3.8 - 1.3$ C1
 $= 2.5(3) \text{ V}$ A1 [2]

Page 4	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2011	9702	23

- 5 (a) transverse waves have vibrations that are perpendicular / normal to the direction of energy travel B1
longitudinal waves have vibrations that are parallel to the direction of energy travel B1 [2]
- (b) vibrations are in a single direction M1
either applies to transverse waves
or normal to direction of wave energy travel
or normal to direction of wave propagation A1 [2]
- (c) (i) 1. amplitude = 2.8 cm B1 [1]
2. phase difference = 135° *or* 0.75π rad *or* $\frac{3}{4}\pi$ rad *or* 2.36 radians (three sf needed)
numerical value M1
unit A1 [2]
- (ii) amplitude = 3.96 cm (4.0 cm) A1 [1]
- 6 (a) (i) greater deflection M0
greater electric field / force on α -particle A1 [1]
- (ii) greater deflection M0
greater electric field / force on α -particle A1 [1]
- (b) (i) *either* deflections in opposite directions because oppositely charged M1
A1
or β less deflection (M1)
 β has smaller charge (A1) [2]
- (ii) α smaller deflection because larger mass M1
A1 [2]
- (iii) β less deflection because higher speed B1 [1]
- (c) *either* $F = ma$ and $F = Eq$ *or* $a = Eq / m$ C1
ratio = *either* $\frac{(2 \times 1.6 \times 10^{-19}) \times (9.11 \times 10^{-31})}{(1.6 \times 10^{-19}) \times 4 \times (1.67 \times 10^{-27})}$
or $[2e \times 1 / 2000 \text{ u}] / [e \times 4u]$ C1
ratio = $1 / 4000$ *or* 2.5×10^{-4} *or* 2.7×10^{-4} A1 [3]