

CAMBRIDGE INTERNATIONAL EXAMINATIONS

Cambridge International Advanced Subsidiary and Advanced Level

MARK SCHEME for the October/November 2015 series

9702 PHYSICS

9702/21

Paper 2 (AS Structured Questions), maximum raw mark 60

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2015 series for most Cambridge IGCSE[®], Cambridge International A and AS Level components and some Cambridge O Level components.

© IGCSE is the registered trademark of Cambridge International Examinations.

Page 2	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2015	9702	21

- 1 (a) temperature
current
(allow amount of substance, luminous intensity) B1 [2]
- (b) (i) 1. $E = (\text{stress/strain}) = [\text{force/area}] / [\text{extension/original length}]$
units of stress: $\text{kg m s}^{-2} / \text{m}^2$ and no units for strain B1
units of E : $\text{kg m}^{-1} \text{s}^{-2}$ A0 [1]
2. units for T : s, l : m and M : kg
 $K^2 = T^2 E / M l^3$ hence units: $\text{s}^2 \text{kg m}^{-1} \text{s}^{-2} / \text{kg}^3 (= \text{m}^{-4})$ C1
units of K : m^{-2} A1 [2]
- (ii) % uncertainty in $E = 4\%$ (for T^2) + 0.6% (for l^3) + 0.1% (for M) + 3% (for K^2)
 $= 7.7\%$ B1
- $E = [(1.48 \times 10^5)^2 \times 0.2068 \times (0.892)^3] / (0.45)^2$
 $= 1.588 \times 10^{10}$ C1
- 7.7% of $E = 1.22 \times 10^9$ C1
- $E = (1.6 \pm 0.1) \times 10^{10} \text{ kg m}^{-1} \text{ s}^{-2}$ A1 [4]
- 2 (a) $p_s = 10^{-12} \text{ (s)}$ or $T = 4 \times 50 \times 10^{-12} \text{ (s)}$ B1
 $v = f\lambda$ or $v = \lambda / T$ C1
 $\lambda = 3.0 \times 10^8 \times 4 \times 50 \times 10^{-12}$ C1
 $= 0.06(0) \text{ m}$ A1 [4]
- (b) $1500 = 3.0 \times 10^8 \times 4 \times \text{time-base setting}$ or $T = 5 \times 10^{-6} \text{ s}$ C1
time-base setting = $1.3 (1.25) \mu\text{s cm}^{-1}$ A1 [2]
- 3 (a) work done is force \times distance moved in direction of force
or
no work done along PQ as no displacement/distance moved in direction of force B1
work done is same in vertical direction as same distance moved in direction of force B1 [2]

Page 4	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2015	9702	21

- 5 (a) progressive: all particles have same amplitude
stationary: no nodes or antinodes or maximum to minimum/zero amplitude B1
- progressive: adjacent particles are not in phase
stationary: waves particles are in phase (between adjacent nodes) B1 [2]
- (b) (i) wavelength 1.2 m (zero displacement at 0.0, 0.60 m, 1.2 m, 1.8 m, 2.4 m)
either peaks at 0.30 m and 1.5 m and troughs at 0.90 m and 2.1 m
or vice versa (but not both) B1
maximum amplitude 5.0 mm B1 [2]
- (ii) 180° or π rad A1 [1]
- (iii) at $t = 0$ particle has kinetic energy as particle is moving B1
at $t = 5.0$ ms no kinetic energy as particle is stationary
so decrease in kinetic energy (between $t = 0$ and $t = 5.0$ ms) B1 [2]
- 6 (a) energy converted from chemical to electrical per unit charge B1 [1]
- (b) (i) current = $E/(R + r)$ C1
 $= 6.0/(16 + 0.5)$
 $= 0.36$ (0.364) A A1 [2]
- (ii) terminal p.d. = $(0.36 \times 16) = 5.8$ V or $(6 - 0.36 \times 0.5)$
 $= 5.8$ V A1 [1]
- (c) (i) use of $R = \rho l/A$ or proportionality with length and inverse
proportionality with area or d^2 C1
 $d/2$ and $l/2$ gives resistance of $Z = 2R_Y = 24$ (Ω) C1
 $R =$ resistance of parallel combination = $[1/24 + 1/12]^{-1}$
 $= 8(.0)$ (Ω) A1 [3]
- (ii) resistance of circuit less therefore current larger B1
lost volts greater therefore terminal p.d. less B1 [2]
- (d) power = $I^2 R$ or VI or V^2/R C1
current in second circuit ($= 6.0/12.5$) = 0.48 (A) B1
ratio = $[(0.36)^2 \times 16] / [(0.48)^2 \times 12] = 0.75$ [0.77 if full s.f. used] B1 [3]

Page 5	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2015	9702	21

7 (a) (i) curved path towards negative (–) plate (right-hand side) B1 [1]

(ii) range of α -particle is only few cm in air/loss of energy of the α -particles due to collision with air molecules/ionisation of the air molecules B1 [1]

(iii) $V = E \times d$ C1

$$= 140 \times 10^6 \times 12 \times 10^{-3} = 1.7 \text{ (1.68) MV} \quad \text{A1 [2]}$$

(b) β have opposite charge to α therefore deflection in opposite direction B1

β has a range of velocities/energies hence number of different deflections B1

β have less mass or q/m is larger hence deflection is greater

or

β with (very) high speed (may) have less deflection B1 [3]

(c)

emitted particle	change in Z	change in A
α -particle	–2	–4
β -particle	+1	0

A1 [1]