Cambridge International AS & A Level

Cambridge International Examinations
Cambridge International Advanced Subsidiary and Advanced Level

PHYSICS **9702/22**

Paper 2 AS Structured Questions **October/November 2016**

MARK SCHEME

Maximum Mark: 60

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2016 series for most Cambridge IGCSE®, Cambridge International A and AS Level components and some Cambridge O Level components.

1 (a) (i) force / area (normal to the force) B1 [1]

(ii) ($p = F/A$ so) units: $\text{kg m s}^{-2} / \text{m}^2 = \text{kg m}^{-1} \text{s}^{-2}$ A1 [1]

allow use of other correct equations:
e.g. ($\Delta p = \rho g \Delta h$ so) $\text{kg m}^{-3} \text{ m s}^{-2} \text{ m} = \text{kg m}^{-1} \text{s}^{-2}$
e.g. ($p = W/\Delta V$ so) $\text{kg m s}^{-2} \text{ m} / \text{m}^3 = \text{kg m}^{-1} \text{s}^{-2}$

(b) units for m: kg, t: s and ρ: kg m^{-3} C1

units of C: $\text{kg} / \text{s} (\text{kg m}^{-3} \text{ kg m}^{-1} \text{ s}^{-2})^{1/2}$
or
units of C^2: $\text{kg}^2 / \text{s}^2 \text{ kg m}^{-3} \text{ kg m}^{-1} \text{ s}^{-2}$ C1

units of C: m^2 A1 [3]

2 (a) $\Delta E = mg\Delta h$ C1

$= 0.030 \times 9.81 \times (-)0.31$

$= (-)0.091$ J A1 [2]

(b) $E = \frac{1}{2}mv^2$ C1

(initial) $E = \frac{1}{2} \times 0.030 \times 1.3^2$ (= 0.0254) C1

$0.5 \times 0.030 \times v^2 = (0.5 \times 0.030 \times 1.3^2) + (0.030 \times 9.81 \times 0.31)$ so $v = 2.8 \text{ m s}^{-1}$
or
$0.5 \times 0.030 \times v^2 = (0.0254) + (0.091)$ so $v = 2.8 \text{ m s}^{-1}$ A1 [3]

(c) (i) $0.096 = 0.030(v + 2.8)$ C1

$v = 0.40 \text{ m s}^{-1}$ A1 [2]

(ii) $F = \Delta p / (\Delta) t$ *or* $F = ma$
$= 0.096 / 20 \times 10^{-3}$ *or* $0.030 (0.40 + 2.8) / 20 \times 10^{-3}$ C1

$= 4.8$ N A1 [2]

(d) <u>kinetic</u> energy (of ball and wall) decreases/changes/not conserved, so inelastic
or
(relative) speed of approach (of ball and wall) not equal to/greater than (relative) speed of separation, so inelastic. B1 [1]

(e) force = work done / distance moved
$= (0.091 - 0.076) / 0.60$ C1

$= 0.025$ N A1 [2]

3 **(a)** resultant force (in any direction) is zero B1
resultant moment/torque (about any point) is zero B1 [2]

(b) **(i)** force = 33 sin 52° *or* 33 cos 38°
= 26 N A1 [1]

(ii) 26×0.30 *or* $W \times 0.20$ *or* 12×0.40 C1

$26 \times 0.30 = (W \times 0.20) + (12 \times 0.40)$ C1

$W = 15$ N A1 [3]

(c) **(i)** $E = \Delta\sigma / \Delta\varepsilon$ *or* $E = \sigma / \varepsilon$ C1

$\Delta\sigma = 2.0 \times 10^{11} \times 7.5 \times 10^{-4}$
$= 1.5 \times 10^{8}$ Pa A1 [2]

(ii) $\Delta\sigma = \Delta F / A$ *or* $\sigma = F / A$ C1

$A = 78 / 1.5 \times 10^{8}$ $(= 5.2 \times 10^{-7}\ \text{m}^2)$ C1

$5.2 \times 10^{-7} = \pi d^2 / 4$

$d = 8.1 \times 10^{-4}$ m A1 [3]

4 **(a)** wave incident on/passes by or through an aperture/edge B1
wave spreads (into geometrical shadow) B1 [2]

(b) **(i)** waves (from slits) overlap (at point X) B1

path difference (from slits to X) is zero/
phase difference (between the two waves) is zero
(so constructive interference gives bright fringe) B1 [2]

(ii) difference in distances = $\lambda / 2 = 580 / 2$
= 290 nm A1 [1]

(iii) $\lambda = ax / D$ C1

$D = [0.41 \times 10^{-3} \times (2 \times 2.0 \times 10^{-3})] / 580 \times 10^{-9}$ C1

= 2.8 m A1 [3]

(iv) same separation/fringe width/number of fringes
bright fringe(s)/central bright fringe/(fringe at) X less bright
dark fringe(s)/(fringe at) Y/(fringe at) Z brighter
contrast between fringes decreases

Any two of the above four points, 1 mark each B2 [2]

5 **(a)** total/sum of electromotive forces or e.m.f.s
= total/sum of potential differences or p.d.s M1
around a loop/(closed) circuit A1 [2]

(b) **(i)** (current in battery =) current in A + current in B *or* $I_A + I_B$ C1

(I =) 0.14 + 0.26 = 0.40 A A1 [2]

(ii) $E = V + Ir$

6.8 = 6.0 + 0.40r *or* 6.8 = 0.40 (15 + r) C1

r = 2.0 Ω A1 [2]

(iii) $R = V / I$ C1

ratio (= R_A / R_B) = (6.0 / 0.14) / (6.0 / 0.26)
= 42.9 / 23.1 *or* 0.26 / 0.14

= 1.9 (1.86) A1 [2]

(iv) **1.** $P = EI$ *or* VI *or* $P = I^2R$ *or* $P = V^2/R$ C1

= 6.8 × 0.40 = 0.40^2 × 17 = 6.8^2 / 17

= 2.7 W (2.72 W) A1 [2]

2. output power = VI
= 6.0 × 0.40 (= 2.40 W) C1

efficiency = (6.0 × 0.40) / (6.8 × 0.40) = 2.40 / 2.72
= 0.88 or 88% (*allow 0.89 or 89%*) A1 [2]

6 **(a)** hadron not a fundamental particle/lepton is fundamental particle
or
hadron made of quarks/lepton not made of quarks
or
strong force/interaction acts on hadrons/does not act on leptons B1 [1]

(b) **(i)** ${}^{0}_{1}e^{(+)}$ or ${}^{0}_{1}\beta^{(+)}$ B1

${}^{0}_{0}\nu_{(e)}$ B1 [2]

(ii) weak (nuclear force / interaction) B1 [1]

(iii)
- mass-energy
- momentum
- proton number
- nucleon number
- charge

Any three of the above quantities, 1 mark each B3 [3]

(c) (quark structure of proton is) up, up, down or uud B1

up/u (quark charge) is (+)⅔(*e*), down/d (quark charge) is –⅓(*e*) C1

⅔*e* + ⅔*e* – ⅓*e* = (+)*e* A1 [3]