

**MARK SCHEME for the October/November 2006 question paper**

**9702 PHYSICS**

**9702/04**

Paper 4 (Core), maximum raw mark 60

This mark scheme is published as an aid to teachers and students, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began.

All Examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

The grade thresholds for various grades are published in the report on the examination for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses.

- CIE will not enter into discussions or correspondence in connection with these mark schemes.

CIE is publishing the mark schemes for the October/November 2006 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



Page 2	Mark Scheme	Syllabus	Paper
	GCE A/AS LEVEL - OCT/NOV 2006	9702	04

1 (a)	<i>either</i> ratio of work done to mass/charge or work done moving unit mass/charge from infinity or both have zero potential at infinity	B1	[1]
(b)	gravitational forces are (always attractive) electric forces can be attractive or repulsive for gravitational, work got out as masses come together /mass moves from infinity for electric, work done on charges if same sign, work got out if opposite sign as charges come together	B1 B1 B1 B1	[4]
2 (a) (i)	idea of heat lost (by oil) = heat gained (by thermometer) $32 \times 1.4 \times (54 - t) = 12 \times 0.18 \times (t - 19)$ $t = 52.4^\circ\text{C}$	C1 C1 A1	[3]
(ii)	<i>either</i> ratio (= 1.6/54) = 0.030 or (=1.6/327) = 0.0049	A1	[1]
(b)	thermistor thermometer (allow 'resistance thermometer') because small mass/thermal capacity	B1 B1	[2]
(c)	boiling point temperature is constant further comment e.g. heating of bulb would affect only rate of boiling	M1 A1	[2]
3 (a)	use of $a = -\omega^2 x$ clear <i>either</i> $\omega = \sqrt{2k/m}$ or $\omega^2 = (2k/m)$ $\omega = 2\pi f$ $f = (1/2\pi)\sqrt{(2 \times 300)/0.240}$ $= 7.96 \approx 8 \text{ Hz}$	C1 B1 C1 B1 A0	[4]
(b) (i)	resonance	B1	[1]
(ii)	8 Hz	B1	[1]
(c)	(increase amount of) damping without altering ( $k$ or) $m$ ... (some indirect reference is acceptable) sensible suggestion	B1 B1 B1	[3]
4 (a) (i)	$\frac{GMm}{\frac{1}{2}m} \{(R + h_1)^{-1} - (R + h_2)^{-1}\}$ $\{v_1^2 - v_2^2\}$	B1 B1	[2]
(b)	$2M \times 6.67 \times 10^{-11} \{(26.28 \times 10^6)^{-1} - (29.08 \times 10^6)^{-1}\} = 5370^2 - 5090^2$ $M \times 4.888 \times 10^{-19} = 2.929 \times 10^6$ $M = 6.00 \times 10^{24} \text{ kg}$ (If equation in (a) is dimensionally unsound, then 0/3 marks in (b), if dimensionally sound but incorrect, treat as e.c.f.)	B1 C1 A1	[3]
5 (a) (i)	(induced) e.m.f proportional/equal to rate of change of flux (linkage) (allow 'induced voltage, induced p.d.') flux is cut as the disc moves hence inducing an e.m.f	B1 M1 A0	[2]
(ii)	field in disc is not uniform/rate of cutting not same/speed of disc not same (over whole disc) so different e.m.f.'s in different parts of disc lead to eddy currents	B1 M1 A0	[2]
(b)	eddy currents dissipate thermal energy in disc energy derived from oscillation of disc energy of disc depends on amplitude of oscillations	B1 B1 B1	[3]

Page 3	Mark Scheme	Syllabus	Paper
	GCE A/AS LEVEL - OCT/NOV 2006	9702	04

- 6 (a) (i) peak voltage =  $6\sqrt{2}$   
peak voltage = 8.48 V C1 A1 [2]
- (ii) zero because *either* no current in circuit (and  $V = IR$ )  
*or* all p.d. across diode B1 [1]
- (b) waveform: half-wave rectification B1  
peak height at about 4.25 cm B1  
half-period spacing of 2.0 cm B1 [3]  
(allow  $\pm\frac{1}{4}$  square for height and half-period)
- (c) (i) capacitor shown in parallel with resistor B1 [1]
- (ii) *either* energy =  $\frac{1}{2}CV^2$  or =  $\frac{1}{2}QV$  and  $Q = CV$  C1  
 $= \frac{1}{2} \times 180 \times 10^{-6} \times (6\sqrt{2})^2$  C1  
 $= 6.48 \times 10^{-3} \text{ J}$  A1 [3]
- (iii) *either* fraction =  $0.43^2$  or final energy = 1.2 mJ C1  
fraction = 0.18 A1 [2]
- 7 (a) (i) quantum/packet/discrete amount of energy M1  
electromagnetic mentioned A1 [2]
- (ii) max. k.e. corresponds to electron emitted from surface B1  
energy is required to bring electron to surface B1 [2]
- (b) at higher frequency, fewer photons (per second) for same intensity M1  
so rate of emission decreases A1 [2]  
(allow argument based on photoelectric efficiency)
- 8 (a) (i) *either* number =  $6.02 \times 10^{23} \times \{(2.65 \times 10^{-6})/234\}$  C1  
*or* number =  $(2.65 \times 10^{-9})/(234 \times 1.66 \times 10^{-27})$  A1 [2]  
 $= 6.82 \times 10^{15}$
- (ii)  $A = \lambda N$  C1  
 $604 = \lambda \times 6.82 \times 10^{15}$   
 $\lambda = 8.86 \times 10^{-14} \text{ s}^{-1}$  A1 [2]
- (iii)  $T_{\frac{1}{2}} = \ln 2 / \lambda$  C1  
 $= 7.82 \times 10^{12} \text{ s}$  A1 [2]  
 $= 2.48 \times 10^5 \text{ years}$
- (b) half-life is (very) long (compared with time of counting) B1 [1]
- (c) there would be appreciable decay of source during the taking of measurements B1 [1]