


January 2007  
6679 Mechanics M3  
Mark Scheme

Question Number	Scheme	Marks
1.	<p>(a) Maximum speed when accel. = 0 (o.e.)</p> <p>(b) <math>\frac{1}{12}(30 - x) = v \frac{dv}{dx}</math> (acceln = ... + attempt to integrate)</p> <p>Use of <math>v \frac{dv}{dx}</math>: <math>\frac{v^2}{2} = \frac{1}{12} \left( 30x - \frac{x^2}{2} \right) (+ c)</math></p> <p>Substituting <math>x = 30</math>, <math>v = 10</math> and finding <math>c</math> (<math>= 12.5</math>), or limits</p> $\underline{v^2 = 25 + 5x - \frac{1}{12}x^2 \text{ (o.e.)}}$	<p>B1 (1)</p> <p>M1 ↓ M1 A1 ↓ M1</p> <p>A1 (5)</p> <p>(a) Allow “acceln &gt; 0 for <math>x &lt; 30</math>, acceln &lt; 0 for <math>x &gt; 30</math>” Also “accelerating for <math>x &lt; 30</math>, decelerating for <math>x &gt; 30</math>” But “acceln &lt; 0 for <math>x &gt; 30</math>” only is B0</p> <p>(b) 1<sup>st</sup> M1 will be generous for wrong form of acceln (e.g. <math>dv/dx</math>)! 3<sup>rd</sup> M1 If use limits, they must use them in correct way with correct values Final A1. Have to accept any expression, but it must be for <math>v^2</math> explicitly (not <math>1/2v^2</math>), and if in separate terms, one can expect like terms to be collected. Hence answer in form as above, or e.g. <math>\frac{1}{12}(300 + 60x - x^2)</math>; also <math>100 - \frac{1}{12}(30 - x)^2</math></p>

2.



$$\text{Height of cone} = \frac{a}{\tan \alpha} = 3a$$

$$\text{Hence } h = \frac{3}{4}a$$

$$\tan \theta = \frac{a}{\frac{3}{4}a} = \frac{4}{3} \Rightarrow \theta = 53.1^\circ$$

M1 A1

↓

M1

↓

M1 A1

(5)

1<sup>st</sup> M1 (generous) allow any trig ratio to get height of cone (e.g. using sin)

3<sup>rd</sup> M1 For correct trig ratio on a suitable triangle to get  $\theta$  or complement (even if they call the angle by another name – hence if they are aware or not that they are getting the required angle)

3	<p>(a) <math>E.P.E. = \frac{1}{2} \frac{3.6mg}{a} x^2 = \frac{1}{2} \frac{3.6mg}{a} \left(\frac{a}{3}\right)^2</math>  <math>= \underline{0.2mga}</math></p> <p>(b) Friction = <math>\mu mg \Rightarrow</math> work done by friction = <math>\mu mg \left(\frac{4a}{3}\right)</math>          Work-energy: <math>\frac{1}{2}m.2ga = \mu mgd + 0.2mga</math> (3 relevant terms)          Solving to find <math>\mu</math>: <math>\underline{\mu = 0.6}</math></p>	M1 A1 A1 (3) M1 A1 M1 A1 ✓ ↓ M1 A1 (6)
---	--	---

4.	(a) Energy: $\frac{1}{2}m.3ag - \frac{1}{2}mv^2 = mga(1 + \cos\theta)$ $v^2 = ag(1 - 2\cos\theta)$ (o.e.)  (b) $T + mg\cos\theta = m\frac{v^2}{a}$  Hence $T = (1 - 3\cos\theta)mg$ (*)  (c) Using $T = 0$ to find $\cos\theta$  Hence height above A = $\frac{4}{3}a$ Accept 1.33a (but must have 3+ s.f.)  (d) $v^2 = \frac{1}{3}ag$ (o.e.) f.t. using $\cos\theta = \frac{1}{3}$ in $v^2$  consider vert motion: $(v\sin\theta)^2 = 2gh$ (with v resolved)  $\sin^2\theta = \frac{8}{9}$ (or $\theta = 70.53$ , $\sin\theta = 0.943$ ) and solve for h (as $ka$ ) $h = \frac{4}{27}a$ or $0.148a$ (awrt)  <b>OR</b> consider energy: $\frac{1}{2}m(v\cos\theta)^2 + mgh = \frac{1}{2}mv^2$ (3 non-zero terms)  Sub for v, θ and solve for h $h = \frac{4}{27}a$ or $0.148a$ (awrt)	M1 A1  A1 (3) M1 A1  A1 cso (3)  M1  A1 (2)  B1 ✓  M1 A1 ↓ M1  A1  M1 A1 ↓ M1  A1
----	--	--

Question Number	Scheme	Marks
5.	<p>(a) <math>\uparrow T \cos \theta = mg</math></p> $\leftrightarrow T + T \sin \theta = mr\omega^2$ $r = h \tan \theta$ $\frac{mg}{\cos \theta} (1 + \sin \theta) = \frac{m\omega^2 h \sin \theta}{\cos \theta}$ $\underline{\omega^2 = \frac{g}{h} \left( \frac{1 + \sin \theta}{\sin \theta} \right)}$ <p style="text-align: right;">(eliminate <math>r</math>)</p> <p style="text-align: right;">(solve for <math>\omega^2</math> )</p>	B1 M1 A1 B1 ↓ M1 ↓ M1 A1 (7)
(b)	$\omega^2 = \frac{g}{h} \left( \frac{1}{\sin \theta} + 1 \right) > \frac{2g}{h}$ ( $\sin \theta < 1$ ) $\Rightarrow \omega > \sqrt{\frac{2g}{h}}$ (*)	M1 A1 (2)
(c)	$\frac{3g}{h} = \frac{g}{h} \left( \frac{1 + \sin \theta}{\sin \theta} \right) \Rightarrow \sin \theta = \frac{1}{2}$ $\underline{T \cos \theta = mg \Rightarrow T = \frac{2\sqrt{3}}{3} mg \text{ or } 1.15mg \text{ (awrt)}}$	M1 A1 ↓ M1 A1 (4)
	<p>(a) Allow first B1 M1 A1 if assume different tensions (so next M1 is effectively for eliminating <math>r</math> <b>and</b> <math>T</math>).</p> <p>(b) M1 requires a <i>valid</i> attempt to derive an <i>inequality</i> for <math>\omega</math>.  (Hence putting <math>\sin \theta = 1</math> immediately into expression of <math>\omega^2</math> [assuming this is the critical value] is M0.)</p>	

6.

(a) Moments:  $\pi \int_1^2 xy^2 dx = V \bar{x}$  or  $\int_1^2 xy^2 dx = \bar{x} \int_1^2 y^2 dx$

$$\int_1^2 y^2 dx = \int_1^2 \frac{1}{4x^4} dx = \left[ -\frac{1}{12x^3} \right]_1^2 (= \frac{7}{96}) \quad (\text{either})$$

$$\int_1^2 xy^2 dx = \int_1^2 \frac{1}{4x^3} dx = \left[ -\frac{1}{8x^2} \right]_1^2 (= \frac{3}{32}) \quad (\text{both})$$

Solving to find  $\bar{x}$  ( $= \frac{9}{7}$ )  $\Rightarrow$  required dist  $= \frac{9}{7} - 1 = \frac{2}{7}$  m (\*)

$\downarrow$   
M1 A1 cso  
(6)

(b)

	$H$	$S$	$T$
Mass	$(\rho) \frac{2}{3} \pi \left(\frac{1}{2}\right)^3$ , $\left[ = \frac{1}{12}(\rho)\pi \right]$	$(\rho) \frac{7\pi}{96}$	$H + S$ $\left[ = \frac{5}{32}(\rho)\pi \right]$

B1, M1

Dist of CM from base  $\frac{19}{16}$  m  $\frac{5}{7}$  m  $\bar{x}$


Moments:  $\left[ = \frac{1}{12}(\rho)\pi \right] \left( \frac{19}{16} \right) + (\rho) \frac{7\pi}{96} \left( \frac{5}{7} \right) = \left[ \frac{5}{32}(\rho)\pi \right] \bar{x}$

M1 A1

$$\bar{x} = \frac{29}{30} \text{ m or } 0.967 \text{ m (awrt)}$$

A1  
(7)

Allow distances to be found from different base line if necessary

7.	<p>(a) </p> $T = \frac{\lambda}{0.8} (0.05) = 0.25g$ $\lambda = \frac{(0.8)(0.25g)}{0.05} = 39.2 \text{ (*)}$	M1 A1 (2)
	<p>(b) <math>T = \frac{39.2}{0.8} (x + 0.05)</math></p> $mg - T = ma$ <p style="text-align: right;">(3 term eqn)</p> $0.25g - \frac{39.2}{0.8} (x + 0.05) = 0.25 \ddot{x} \text{ (or equivalent)}$ $\ddot{x} = -196x$ <p style="text-align: right;">↓</p> <p>SHM with period <math>\frac{2\pi}{\omega} = \frac{2\pi}{14} = \frac{\pi}{7} \text{ s}</math> (*)</p>	M1 M1 A1 A1 M1 A1 cso (6)
	<p>(c) <math>v = 14 \sqrt{\{(0.1)^2 - (0.05)^2\}}</math></p> $= 1.21(24...) \approx \underline{1.21 \text{ m s}^{-1}}$ <p style="text-align: right;">(3 s.f.) Accept <math>7\sqrt{3}/10</math></p>	A1 (3)
	<p>(d) Time <math>T</math> under gravity <math>= \frac{1.21..}{g}</math> (<math>= 0.1237 \text{ s}</math>)</p> <p>Complete method for time <math>T'</math> from <math>B</math> to slack.</p> <p>[↑ e.g. <math>\frac{\pi}{28} + t</math>, where <math>0.05 = 0.1 \sin 14t</math></p> <p style="text-align: center;">OR <math>T'</math>, where <math>-0.05 = 0.1 \cos 14T'</math> ]</p>	B1√ M1 A1
	$T'' = 0.1496 \text{ s}$	A1
	<p>Total time <math>= T + T' = \underline{0.273 \text{ s}}</math></p>	A1 (5)
(b)	<p>1<sup>st</sup> M1 must have extn as <math>x + k</math> with <math>k \neq 0</math> (but allow M1 if e.g. <math>x + 0.15</math>), or must justify later</p> <p>For last four marks, <i>must</i> be using <math>\ddot{x}</math> (not <math>a</math>)</p>	
	<p>(c) Using <math>x = 0</math> is M0</p> <p>(d) M1 – must be using distance for when string goes slack. Using <math>x = -0.1</math> (i.e. assumed end of the oscillation) is M0</p>	