

Mark Scheme (Standardisation) January 2010

GCE

GCE Physics (6PH07/1)

Edexcel Limited. Registered in England and Wales No. 4496750 Registered Office: One90 High Holborn, London WC1V 7BH



General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

Mark scheme notes

Underlying principle

The mark scheme will clearly indicate the concept that is being rewarded, backed up by examples. It is not a set of model answers.

For example:

(iii) Horizontal force of hinge on table top

66.3 (N) or 66 (N) and correct indication of direction [no ue] [Some examples of direction: acting from right (to left) / to the left / West / opposite direction to horizontal. May show direction by arrow. Do not accept a minus sign in front of number as direction.]

This has a clear statement of the principle for awarding the mark, supported by some examples illustrating acceptable boundaries.

- 1. Mark scheme format
 - 1.1 You will not see 'wtte' (words to that effect). Alternative correct wording should be credited in every answer unless the ms has specified specific words that must be present. Such words will be indicated by underlining e.g. 'resonance'

✓

1

- 1.2 Bold lower case will be used for emphasis.
- 1.3 Round brackets () indicate words that are not essential e.g. "(hence) distance is increased".
- 1.4 Square brackets [] indicate advice to examiners or examples e.g. [Do not accept gravity] [ecf].
- 2. Unit error penalties
 - 2.1 A separate mark is not usually given for a unit but a missing or incorrect unit will normally cause the final calculation mark to be lost.
 - 2.2 Incorrect use of case e.g. 'Watt' or 'w' will not be penalised.
 - 2.3 There will be no unit penalty applied in 'show that' questions or in any other question where the units to be used have been given.
 - 2.4 The same missing or incorrect unit will not be penalised more than once within one question but may be penalised again in another question.
 - 2.5 Occasionally, it may be decided not to penalise a missing or incorrect unit e.g. the candidate may be calculating the gradient of a graph, resulting in a unit that is not one that should be known and is complex.
 - 2.6 The mark scheme will indicate if no unit error penalty is to be applied by means of [no ue].
- 3. Significant figures
 - 3.1 Use of an inappropriate number of significant figures in the theory papers will normally only be penalised in 'show that' questions where use of too few significant figures has resulted in the candidate not demonstrating the validity of the given answer.
 - 3.2 Use of an inappropriate number of significant figures will normally be penalised in the practical examinations or coursework.
 - 3.3 Using $g = 10 \text{ m s}^{-2}$ will not be penalised.
- 4. Calculations
 - 4.1 Bald (i.e. no working shown) correct answers score full marks unless in a 'show that' question.
 - 4.2 If a 'show that' question is worth 2 marks then both marks will be available for a reverse working; if it is worth 3 marks then only 2 will be available.
 - 4.3 use of the formula means that the candidate demonstrates substitution of physically correct values, although there may be conversion errors e.g. power of 10 error.
 - 4.4 recall of the correct formula will be awarded when the formula is seen or implied by substitution.
 - 4.5 The mark scheme will show a correctly worked answer for illustration only.
 - 4.6 Example of mark scheme for a calculation:

'Show that' calculation of weight

Use of L × W × H

Substitution into density equation with a volume and density

Correct answer [49.4 (N)] to at least 3 sig fig. [No ue] [Allow 50.4(N) for answer if 10 N/kg used for g.] [If 5040 g rounded to 5000 g or 5 kg, do not give 3rd mark; if conversion to kg is omitted and then answer fudged, do not give 3rd mark] [Bald answer scores 0, reverse calculation 2/3]

3

Example of answer:

80 cm × 50 cm × 1.8 cm = 7200 cm³ 7200 cm³ × 0.70 g cm⁻³ = 5040 g 5040 × 10⁻³ kg × 9.81 N/kg = 49.4 N

- 5. Quality of Written Communication
 - 5.1 Indicated by QoWC in mark scheme, placed as first mark.
 - 5.2 Usually it is part of a max mark.
- 6. Graphs
 - 6.1 A mark given for axes requires both axes to be labelled with quantities and units, and drawn the correct way round.
 - 6.2 Sometimes a separate mark will be given for units or for each axis if the units are complex. This will be indicated on the mark scheme.
 - 6.3 A mark given for choosing a scale requires that the chosen scale allows all points to be plotted, spreads plotted points over more than half of each axis and is not an awkward scale e.g. multiples of 3, 7 etc.
 - 6.4 Points should be plotted to within 1 mm.
 - Check the two points furthest from the best line. If both OK award mark.
 - If either is 2 mm out do not award mark.
 - If both are 1 mm out do not award mark.
 - If either is 1 mm out then check another two and award mark if both of these OK, otherwise no mark.
 - 6.5 For a line mark there must be a thin continuous line which is the best-fit line for the candidate's results.

Question	Answer	Mark
Number		
1.	С	1
2 (a)	D	1
(b)	В	1
(C)	A	1
3.	D	1
	Total	5
Question	n • Answer	 Mark

Number		
Number 4(a)	 [Marks can be from text or diagram] Max 3 from Means of measuring height (1) Means of determining speed (1) Equates (final) GPE with (final) KE (1) Method to determine KE after bounce (1) Description of appropriate experimental method (1) States that mass cancels OR mass stays the same OR mass measured OR mass known (1) Indication of how (percentage) energy loss will be determined (1) States sensible precaution (1) Example of answer Drops ball of known mass vertically from known height Determines height of bounce using a metre rule States mgΔh = 1/2mv² % loss in KE = loss in PE x 100% initial PE 	• • • • • • • • • • • • • •
	• Precaution: make measurement of height of bounce at eye level	
•	• I otal	• 5

 Question Number	Answer	• Mark
• 5.(a)	 Correct circuit with constantan wire, variable resistor and supply (1) Ammeter in series and voltmeter in parallel (1) 	• 2 •
• (b) (i) • (ii)	 Find gradient which is R (1) Max 1 from 	• 1 •
	 Graph enables an average result to be taken (1) Graph will show anomalies(1) Graph will show if resistance changes (1) 	• Max 1
• (c)	 Metre rule/tape(1) Longer length so measurement to nearest mm appropriate (1) [allow to nearest ¹/₂ mm] 	• • 2
• (d) (i) • (ii)	• <u>Diameter</u> (1) • Find area using $A = \pi d^2/4$ or $A = \pi r^2$ [stated or implied](1) • Calculate ρ using $R = \rho l/A$ (1)	• 3 •
•	Total	• 9

QuestionNumber	Answer	• Mark
• 6(a)	 Vertical length of wire with masses on end OR horizontal wire with masses over pulley (1) Measure extension (1) Further detail (1) e.g. use of mark on wire OR use of F = k∆x OR extension = final – initial length OR comparison of wires 	• • 3
• (b)	• (Initial) <u>length</u> of wires (1)	• 1
• (C)	 Use of goggles OR means of catching/avoiding falling masses (1) Protection (of eyes) from snapping wire OR protection of feet/floor from falling masses (1) 	• • 2
• (d)	 k chosen so that wire wont stretch or break for a given picture (1) 	• 1
•	Total	• 7

 Question Number	Answer	• Mark
• 7 (a)	 Max 3 from Inconsistent precision of timing(1) Lengths only recorded to nearest 10 cm (1) Only 10 oscillations timed (1) Too few values(1) No repeats(1) Small range(1) 	• Max 3
• (b)	 Correct values of T² with units of s² (1) Values of T² to 2/3 sig figs [ignore sig figs for first value] (1) Axes labelled with quantity and unit [allow ecf from table](1) Suitable scale showing origin OR 4 - 8 for T² and 1.0 - 1.8 for l (1) Correct plotting (1) Line of best fit drawn (1) Example of answer T²/s² OR T²/s² 4(.00) 4(.0) 4.88 4.9 5.66 5.7 6.45 6.5 7.29 7.3 	• • • 6
• (c)	• States $T^2 = \underline{4\pi}^2 l$ and compares with $y = mx + c$ • OR States $T^2 = \underline{4\pi}^2 l$ and states T^2 proportional to l	• • 1
• (d)	 Large triangle [at least half drawn line used in both directions] (1) Correctly calculated value of g in range 9.6 to 9.8 with unit (1) Correct value of g to 2 or 3 sig figs (1) 	• • • 3

• (e)	 Correct calculation of percentage different from own result (1) Example of answer (9.81 - 9.70) x 100 % = 1.1 % 9.81 	• 1
•	Total	• 14