



Examiners' Report June 2016

IAL Physics 3 WPH03 01



Edexcel and BTEC Qualifications

Edexcel and BTEC qualifications come from Pearson, the UK's largest awarding body. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at <u>www.edexcel.com</u> or <u>www.btec.co.uk</u>.

Alternatively, you can get in touch with us using the details on our contact us page at <u>www.edexcel.com/contactus</u>.



Giving you insight to inform next steps

ResultsPlus is Pearson's free online service giving instant and detailed analysis of your students' exam results.

- See students' scores for every exam question.
- Understand how your students' performance compares with class and national averages.
- Identify potential topics, skills and types of question where students may need to develop their learning further.

For more information on ResultsPlus, or to log in, visit <u>www.edexcel.com/resultsplus</u>. Your exams officer will be able to set up your ResultsPlus account in minutes via Edexcel Online.

Pearson: helping people progress, everywhere

Pearson aspires to be the world's leading learning company. Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at: www.pearson.com/uk.

June 2016

Publications Code WPH03_01_1606_ER

All the material in this publication is copyright © Pearson Education Ltd 2016

Introduction

This paper examines practical skills for overseas candidates. Some of the criteria are derived from the criteria which have been used for coursework for home centres.

The best answers showed familiarity with practical investigations and apparatus and, the need in a paper testing practical skills, for the use of appropriate numbers of significant figures. While most candidates realised that it is important to read the introduction to questions carefully and to address the tasks set, some penalised themselves by not using scientific terms or by quoting published mark schemes from previous years which were for different questions.

Q 1-5

The multiple-choice questions were generally answered well, although questions 2 and 3 had lower mean marks.

Question 6

Question 6(a) was straightforward for most students. Most identified the limits of the range; a few chose simply to state its magnitude.

Question 6(b) enabled most students to show sound technique when calculating the percentage uncertainty. Fewer could express their result using an appropriate number of significant figures.

Many responses to question 6(c) included an appropriate improvement to the method, but omitted proper comment as to why it was necessary. Students who mentioned uncertainty tended to refer back to the stated uncertainty in the reaction time itself, rather than focusing on reaction time as the cause of an unacceptably high percentage uncertainty in the 3 s time measurement. Few calculated this percentage uncertainty caused by reaction time, but most did suggest a suitable alternative technique.

- 6 A student's uncertainty in recording her reaction time was ± 0.03 s. She recorded a reaction time of 0.38 s.
 - (a) What was the range of her measurements?



(b) Calculate the percentage uncertainty in her measurement.



(c) The student plans to use a stopwatch to measure the time taken for a trolley to move down a slope. She estimates this time to be about 3 s. Comment on her plan.



4 IAL Physics 3 WPH03 01





The candidate could use bullet points to confine the answer to the space provided. The number of lines provided is a good guide to the length of the answer required.

Question 7

Most of the plans were laid out clearly and showed familiarity with the necessary techniques. A few students offered a prepared response that addressed the requirements of a different experiment.

In their response to part (a), most students showed or listed all the apparatus, although some omitted to include a suitable light source. A few students struggled to name the protractor correctly.

The diagram usually showed the correct angles labeled for part (b). Nearly all students included a correctly drawn normal.

There was some evidence in responses to part (c) of confusion over the precision of a protractor. Many students gave this precision incorrectly as $\pm 0.1^{\circ}$.

The markings on a protractor are often about 1 mm apart and several students appeared to interpret this as a curved millimeter scale, giving the precision as ± 1 mm.

Most students realized that it would be sensible to repeat the readings. Fewer included a comment in their response to part (d) as to why this would be appropriate.

Most students gave excellent responses to part (e), explaining clearly how they would use the data to draw a graph and determine the refractive index. Some simply quoted the refractive index relationship from the data pages, without explaining how they would use it.

Very few students identified an acceptable main source of systematic error in their response to part (f).

Relatively few students could give acceptable comments on safety in their response to part (g). Many answers included inappropriate precautions against broken glass or falling weights.

7 A student is asked to determine the refractive index of glass.

Write a plan for this experiment that uses a rectangular glass block, standard laboratory apparatus and a graphical method.

You should:

- (a) draw a labelled diagram of the apparatus to be used and list any additional apparatus needed,
- (b) show on your diagram the quantities to be measured,

(2)

(2)

(1)

(3)

(2)

- (c) explain your choice of measuring instrument for one of these quantities,
- (d) comment on whether repeat readings are appropriate in this case,
- (e) explain how to determine the refractive index,
- (f) identify the main source of uncertainty and/or systematic error,

(1)

(g) comment on safety. (1)

6 IAL Physics 3 WPH03 01

white paper. ray box Rectangulars glass block for tractor light ray Boston to measure angle angle of i and ro to be measured where i sangle of incidence and r = angle of refraction c) fraction Protractor again measure to a precision 1° and is adequate range of angle which is 1- 92 180° for this experiment. Repeat readings in appropriate to get a more accurate d, results e) Record results for i and r. Calculate sin i and sin r Plot a graph of sin i against sin r and draw a line of best fit. Calculate the gradient of the graph where the gradient of the graph is the refractive index. f) lorallax error may occur when taking the reading on the protocotor



Results Plus Examiner Comments

The emergent angle is correctly marked as equal to the angle of incidence.

In (d) the candidate did not say that the reading would be averaged and therefore was not awarded the mark.

The candidate did not get the mark for (f) as protractors are made with markings on the base to prevent parallax error. This was not widely understood.



A sketch of the graph to be drawn would be a good addtion in part (e).

Another good answer.

Glass block A ruler, pencil, protractor and poner supply will also be needed. A sheet of paper sing may be placed under the glass block to trace the rays of light. b) it is the angle of mander incidence which shald be neared between the normal and the ray of light entering the block 'r' is the angle of refraction and shall be measured between the named and the refracted light ray. () A protector shald be used to measure the angle of inidence as it allows a large angle (up to 280° depending on the protractor) to be measured with a precition of 1°. d) Yes, repeat reachings many he taken to form an anerooge and increase reliability. This is because none of the components are affected in a many that could alter the results by being left on for prolonged den periods of time.

e) And Multiple readings should be taken by morning the light ber which will vary the angle of incidence and allow the corresponding angles of refraction to be taken. A table of the lase sine of i and the Sine of - Chald be drawn up. A grafth of the sin (i) on the y-anis against sin (r) on the x-axis shald be platted where the gradient will be equal to the refractive index of the glass. 3) The main source of unce tainty will come from the measurements of the angles i and a due to the peribitity possibility of parollas error. Readings Stated Should be taken at eye level to amoid this. 9) This experiment poles a low rick as the a potential difference of the pomen supply is quite low. Students Ehold not touch the light best as it will stated up during larger periods of use. **Examiner Comments** This candidate has said that repeat readings would be averaged.

Remember to use a ruler for diagrams, like this candidate.

Examiner Tip

Question 8 (a)

Most students correctly identified a micrometer as an appropriate instrument for measuring the diameter of the wire and gained a mark for part (a). Fewer went on to point out that the measurement should be repeated in such a way as to take account of irregularities in the shape or thickness of the wire.

A good answer.

- 8 In an experiment to determine the resistivity of the material of a wire, a student measured the diameter of the wire to be 0.56×10^{-3} m.
 - (a) Describe how the student should measure the diameter of the wire.

The student should measure the diameter of the wire at different places & of the wire, record the diameters and then take average. **Phis Examiner Comments Examiner Tip** This gained both marks. It is important to identify good measurement techniques.

Another good answer.

- 8 In an experiment to determine the resistivity of the material of a wire, a student measured the diameter of the wire to be 0.56×10^{-3} m.
 - (a) Describe how the student should measure the diameter of the wire.

(2)

(2)

The diameter showed be measured using a micrometer screw gauge with a precision of 0.01 mm to marries accuracy. The diameter can be measured at different points of the unre and while rotating it as well after which the mean of the diameter readings should be noted.





Question 8 (b) (i)

Nearly all the students were able to criticise the table of results appropriately. A few students omitted to target their comment about inconsistent precision to the relevant column of data.

A good answer.

Length / m	Potential difference / V	Resistance / Ω
1.00	0.52	4.72
0.80	0.41	372
0.60	0.27	2.45
0.40	0.19	1.72
0.20	0.1	0.90

(b) During this experiment, the student kept the current constant at 0.11 A and recorded the following results.

(i) Criticise his results.

(2)

A small number of readings have been taken. No repeate or averages can be seen. There is also a slight-inconsistency in precision of the last value of potential difference (the signifigant figures not the same).





In a question about practical experiments use of the appropriate number significant figures is essential. This answer displays unfamiliarity with practical situations.

(b) During this experiment, the student kept the current constant at 0.11 A and recorded the following results.

Length / m	Potential difference / V	Resistance / Ω
1.00	0.52	4,73
0.80	0.41	3.73
0.60	0.27	2.45
0.40	0.19	1.73
0.20	0.1	0.91

(i) Criticise his results.

The gaps between the length welves recorded is big and the gap between the woltage values - is not equal!





Remember that in an experiment the dependant variable does not always increase in equal steps.

(2)

Question 8 (b) (ii)

Although many students gave an appropriate suggestion as to how the current should be kept constant, a significant number gave incorrect responses.

This is an example of a poor response.



This is a good answer.

(ii) Suggest how the student could keep the current constant.

1

Question 8 (b) (iii) - (c) (iii)

Nearly all students drew a good graph for part (c)(i). The most common fault seen was an unbalanced line of best fit. Some students overlooked the examiner's expectation of a suitable scale (with intervals of 1, 2 or 5) and produced a scale with 3 cm intervals.

Most responses to part (c)(ii) showed skilful calculations of gradient. Some students constructed a small triangle that made use of less than half of their drawn line. Careless use of significant figures was evident in a few cases.

Many students answered part (c)(iii) with a successful calculation of the resistivity. Some students were unable to rearrange the equation $R = \rho I/A$ properly and others substituted the cross-sectional area of the wire incorrectly. A large minority of students omitted or mistook the unit for resistivity.

Length / m	Potential difference / V	Resistance / Ω
1.00	0.52	4.70
0.80	0.41	3.7
0.60	0.27	2.5
0.40	0.19	1.7
0.20	0.1	0.91

This was an excellent answer.

(c) (i) Plot a graph of resistance on the *y*-axis and length on the *x*-axis and draw a line of best fit.





Length/m

(ii) Determine the gradient of the graph.

(2)
Gradiewi =
$$\underline{A}\underline{Y} = \underline{A}\underline{R} = \underline{4}.\underline{5} = \underline{4}.\underline{5}^{-1}\underline{4}.\underline{5}^{-1}\underline{4}.\underline{5}^{-1}\underline{4}.$$

Gradient = $\underline{4}.\underline{5}\underline{5}\underline{1}\underline{m}\underline{n}\underline{1}$
(ii) Use your value for the gradient to calculate a value for the resistivity.
(4)
 $R = \rho \underline{1} \quad \underline{Y} = R, \quad \underline{2} = \underline{1}, \quad \underline{m} = \underline{\rho} \quad \underline{A} = \underline{T}\underline{d}\underline{2}^{2}, \quad \underline{A} = \underline{T}\underline{X}(\underline{0}.\underline{5}\underline{5}\underline{X}\underline{1}\underline{0}\underline{3})^{\perp}\underline{4}$
 $A = \underline{2}.\underline{4}\underline{6}\underline{X}\underline{1}\underline{0}\underline{2}^{-1}\underline{m}\underline{2}$
 $\underline{A} = \underline{2}.\underline{4}\underline{6}\underline{X}\underline{1}\underline{0}\underline{2}^{-1}\underline{m}\underline{2}$
 $\underline{A} = \underline{2}.\underline{4}\underline{6}\underline{X}\underline{1}\underline{0}\underline{2}^{-1}\underline{m}\underline{2}$
 $\underline{A} = \underline{2}.\underline{4}\underline{6}\underline{X}\underline{1}\underline{0}\underline{2}\underline{1}\underline{m}$
 $Resistivity = \underline{1}.\underline{12}\underline{X}\underline{1}\underline{0}\underline{2}\underline{M}\underline{m}.$
Resistivity = $\underline{1}.\underline{12}\underline{X}\underline{1}\underline{0}\underline{2}\underline{M}\underline{m}.$
For the gradient the candidate has used, as required, a triangle
which is greater than half the drawn line.

For the gradient the candidate has used, as required, a triangle
The Source Sourc

Question 8 (c) (iv)

Most students responded well to part (c)(iv), showing a good understanding of likely causes of difference between the calculated result and the accepted value.

Paper Summary

Based on their performance on this paper, candidates are offered the following advice:

- Read the question carefully
- Draw scientific diagrams rather than pictures.
- Make sure you have a pencil with a sharp point
- Line of best fit can be a curve
- Don't force a straight line on a graph through the origin
- Remember to justify assertions

Grade Boundaries

Grade boundaries for this, and all other papers, can be found on the website on this link: http://www.edexcel.com/iwantto/Pages/grade-boundaries.aspx





Llywodraeth Cynulliad Cymru Welsh Assembly Government



Pearson Education Limited. Registered company number 872828 with its registered office at 80 Strand, London WC2R 0RL.